



1 Bruce Saunders Way,
 Wolseley SK S0G 5H0
 Phone: (306) 620-2362
 Email: contact@banico.ca
banico.ca



DIMENSIONS	BANI CL 3600
Operating height, max, 60" (1.5 m) bucket	129.62 in
Hinge pin height, max	95.75 in
Overall height of machine	58.2" w/o Joysticks 61.8" with Joystick
Overall length of machine, with 44" (1.5 m) bucket	112 in
Overall length of loader, no attachment	77.625 in
Wheelbase/track length	46.25 in
Dump height, max, with standard bucket	65.47 in
Reach fully raised, 44" (1.5 m) bucket	21 in
Ground clearance, min (center)	9.7 in
Angle of departure	40.5
Bucket rollback angle, ground level	25°
Bucket rollback angle, full height	96°
Dump angle, standard bucket	33°
Bucket width, max	64 in
Bucket width, min	43.75 in
Track width	43.375 in
Unit width, excluding tracks	41.53 in
Swing radius, max, with 60" (1.5 m) bucket	57.88 in
Swing radius, no attachment	41.92 in
Rear overhang, max	21.88 in
Performance	
Ground drive speed, forward and reverse	4.9 mph
Ground pressure, 10.4" (265 mm) tracks	4.15 psi
Includes machine weight, 175-lb (80-kg) bucket, 165-lb (75-kg) operator	
Tipping capacity	3600 lb
Operating capacity (35% of tipping capacity)	1260 lb

BANI CL3600 - MINI SKID STEER

Machine weight (fluids full)	3270 lb
Fluid Capacities	
Fuel tank	9.2 gal
Hydraulic reservoir	23.6 gal
Power	
KOHLER Diesel KSD KSD 1403TC	US Tier 4 EU Stage V
Number of cylinders	3
Displacement	84.88 in ³
Bore	3.2 in
Stroke	3.5 in
Manufacturer's gross power rating (per SAE J1955)	25.7 hp
Rated engine speed	3000rpm
Hydraulic System	
	Hydrastatic Pump
Flow rate (high)	12.6 GPM
Pressure	3000 psi